





BUILDING BETTER.

STOCK ITEM CATALOG



PHOENIX FACILITY

1251 South 35th Avenue, Phoenix, AZ 85009

CATALOG INDEX

Item Description	Page #
Spiral Pipe	3
Adjustable Elbows	4-5
T-Wyes	6
Damper Sleeves	7
Reducers	8
Ceiling Boxes	9
End Caps	9
Start Collars	10
Flex Duct	11
Duct Tape	12
Drill Screws	12
Hanger Strap	12
Duct Wrap	12
Duct Sealer	12

S PIPE 10' • 5' • 3' LENGTHS



8.5" wide strip. S (SMACNA) pipe is the lowest cost pipe we offer and it is very easy to handle.

**Optional factory crimp & bead eliminates the need for a coupling, reducing material & labor costs.

Size	Gauge	10' Part #	5' Part #	3' Part #	QTY	LENGTH
6"	28	S10-B-06	S5-B-06	S3-B-06		
7"	28	S10-B-07	S5-B-07	S3-B-07		
8"	28	S10-B-08	S5-B-08	S3-B-08		
9"	28	S10-B-09	S5-B-09	S3-B-09		
10"	28	S10-B-10	S5-B-10	S3-B-10		
12"	28	S10-B-12	S5-B-12	S3-B-12		
14"	28	S10-B-14	S5-B-14	S3-B-14		
16"	26	S10-C-16	S5-C-16	S3-C-16		
18"	26	S10-C-18	S5-C-18	S3-C-18		
20"	26	S10-C-20	S5-C-20	S3-C-20		
22"	26	S10-C-22	S5-C-22	S3-C-22		
24"	26	S10-C-24	S5-C-24	S3-C-24		
26"	24	S10-D-26	S5-D-26	S3-D-26		
28"	24	S10-D-28	S5-D-28	S3-D-28		

90° - 4 GORE



90 Degree, 4 gore adjustable assembly from 3" to 20" diameters. 22" Diameter and above are 90 degree, 5 gore adjustable assembled. Crimped one end.

*Stainless Steel and Aluminum available upon request

Size	Gauge	Part #	QTY
3"	26	90-C-03	
4"	26	90-C-04	
5"	26	90-C-05	
6"	26	90-C-06	
7"	26	90-C-07	
8"	26	90-C-08	
9"	26	90-C-09	
10"	26	90-C-10	
12"	26	90-C-12	
14"	24	90-D-14	
16"	24	90-D-16	
18"	24	90-D-18	
20"	24	90-D-20	
22"	24	90-D-22	
24"	24	90-D-24	
26"	24	90-D-26	
28"	22	90-E-28	

45° - 2 GORE



45 Degree 2 gore adjustable assembly from 3" to 20" diameters., 22" Diameter and above are 45 degree, 3 gore adjustable assembled. Crimped one end.

*Stainless Steel and Aluminum available upon request

Size	Gauge	Part #	QTY
3"	26	45-C-03	
4"	26	45-C-04	
5"	26	45-C-05	
6"	26	45-C-06	
7"	26	45-C-07	
8"	26	45-C-08	
9"	26	45-C-09	
10"	26	45-C-10	
12"	26	45-C-12	
14"	24	45-D-14	
16"	24	45-D-16	
18"	24	45-D-18	
20"	24	45-D-20	
22"	24	45-D-22	
24"	24	45-D-24	
26"	24	45-D-26	
28"	22	45-E-28	

LONG RADIUS 90° - 5 GORE



90 Degree, 5 gore long radius adjustable assembly from 4" to 18" diameters. Crimped one end. 1.5 to 1 centerline radius.

*Stainless Steel and Aluminum available upon request

Size	Gauge	Part #	QTY
4"	26	90LR-C-04	
5"	26	90LR-C-05	
6"	26	90LR-C-06	
7"	26	90LR-C-07	
8"	26	90LR-C-08	
9"	26	90LR-C-09	
10"	26	90LR-C-10	
12"	26	90LR-C-12	
14"	24	90LR-D-14	
16"	24	90LR-D-16	
18"	24	90LR-D-18	

LONG RADIUS 45° - 3 GORE



45 Degree 3 gore long radius adjustable assembly from 3" to 20" diameters. Crimped one end. 1.5 to 1 centerline radius.

*Stainless Steel and Aluminum available upon request

Size	Gauge	Part #	QTY
4"	26	45LR-C-04	
5"	26	45LR-C-05	
6"	26	45LR-C-06	
7"	26	45LR-C-07	
8"	26	45LR-C-08	
9"	26	45LR-C-09	
10"	26	45LR-C-10	
12"	26	45LR-C-12	
14"	24	45LR-D-14	
16"	24	45LR-D-16	
18"	24	45LR-D-18	

STOCK T-WYES



All stock T-Wyes are spot welded with female/male/male ends. They are fabricated from galvanized steel meeting ASTM-A-653-96 standards.

Size	Gauge	Part #	QTY
8x6x6	26	Y-C-080606	
8x8x6	26	Y-C-080806	
8x8x8	26	Y-C-080808	
10x6x6	26	Y-C-100606	
10x8x6	26	Y-C-100806	
10x8x8	26	Y-C-100808	
10x10x6	26	Y-C-101006	
10x10x8	26	Y-C-101008	
10x10x10	26	Y-C-101010	
12x8x8	26	Y-C-120808	
12x10x6	26	Y-C-121006	
12x10x7	26	Y-C-121007	
12x10x8	26	Y-C-121008	
12x10x10	26	Y-C-121010	
12x12x10	26	Y-C-121210	
12x12x12	26	Y-C-121212	
14x10x10	26	Y-C-141010	
14x12x8	26	Y-C-141208	
14x12x10	26	Y-C-141210	
14x12x12	26	Y-C-141212	
14x14x8	26	Y-C-141408	

PHOENIX



Custom sizes and gauges available upon request.

Available with Jiffy dampers installed upon request.

Size	Gauge	Part #	QTY
14x14x10	26	Y-C-141410	
14x14x12	26	Y-C-141412	
16x10x10	26	Y-C-161010	
16x12x10	26	Y-C-161210	
16x12x12	26	Y-C-161212	
16x14x8	26	Y-C-161408	
16x14x10	26	Y-C-161410	
16x14x12	26	Y-C-161412	
16x14x14	26	Y-C-161414	
16x16x10	26	Y-C-161610	
16x16x12	26	Y-C-161612	
16x16x12	26	Y-C-161612	
18x14x12	26	Y-C-181412	
18x14x14	26	Y-C-181414	
18x16x10	26	Y-C-181610	
18x16x12	26	Y-C-181612	
18x16x14	26	Y-C-181614	
18x16x16	26	Y-C-181616	
18x18x10	26	Y-C-181810	
20x16x16	26	Y-C-201616	
20x18x16	26	Y-C-201816	

STOCK DAMPER SLEEVES

PHOENIX

SLEEVE - DAMPER



Sleeves with 2" stand off, 3/8" aluminum rod with tack welded hat sections. Sleeve is crimped on one end. All sleeves fabricated from galvanized steel meeting ASTM-A-653-96 standards.

Size	Gauge	Part #	QTY
6"	24	DS2.0-06	
7"	24	DS2.0-07	
8"	24	DS2.0-08	
9"	24	DS2.0-09	
10"	24	DS2.0-10	
12"	24	DS2.0-12	
14"	24	DS2.0-14	
16"	24	DS2.0-16	
18"	24	DS2.0-18	

SLEEVE - JIFFY DAMPER



Sleeves feature Duro-Dyne RS256 Jiffy hardware. All sleeves fabricated from galvanized steel meeting ASTM-A-653-96 standards.

Size	Gauge	Part #	QTY
4"	26	DS-04	
5"	26	DS-05	
6"	26	DS-06	
7"	26	DS-07	
8"	26	DS-08	
9"	26	DS-09	
10"	26	DS-10	
12"	26	DS-12	
14"	24	DS-14	
16"	24	DS-16	
18"	24	DS-18	

3-PIECE REDUCERS



Stock 3-piece reducers have a 6" taper and 3" long collars on both ends. All 3-piece reducers are fabricated from galvanized steel meeting ASTM-A-653-96 standards in accordance with SMACNA gauge and construction standards.

Size	Gauge	Part #	QTY
6x4	26	R06-C-0604	
6x5	26	R06-C-0605	
8x6	26	R06-C-0806	
8x7	26	R06-C-0807	
9x7	26	R06-C-0907	
9x8	26	R06-C-0908	
10x6	26	R06-C-1006	
10x7	26	R06-C-1007	
10x8	26	R06-C-1008	
10x9	26	R06-C-1009	
12x8	26	R06-C-1208	
12x9	26	R06-C-1209	
12x10	26	R06-C-1210	
14x8	26	R06-C-1408	
14x9	26	R06-C-1409	
14x10	26	R06-C-1410	
14x12	26	R06-C-1412	

Size	Gauge	Part #	QTY
16x10	24	R06-D-1610	
16x12	24	R06-D-1612	
16x14	24	R06-D-1614	
18x14	24	R06-D-1814	
18x16	24	R06-D-1816	
20x16	24	R06-D-2016	
20x18	24	R06-D-2018	
22x20	24	R06-D-2220	
24x22	24	R06-D-2422	

STOCK CEILING BOXES & END CAPS

PHOENIX

CEILING BOXES



Ceiling boxes have a 4" high can plus a 3" high collar and a plaster ground. Fabricated from galvanized steel meeting ASTM-A-653-96 standards in accordance with SMACNA gauge and construction standards.

Size	Gauge	Part #	QTY
6x6x5	26	CB-060605	
6x6x6	26	CB-060606	
8x8x6	26	CB-080806	
8x8x7	26	CB-080807	
8x8x8	26	CB-080808	
10x10x6	26	CB-101006	
10x10x8	26	CB-101008	
10x10x10	26	CB-101010	
12x12x6	26	CB-121206	
12x12x8	26	CB-121208	
12x12x10	26	CB-121210	
12x12x12	26	CB-121212	
14x14x10	26	CB-141410	
14x14x12	26	CB-141412	
14x14x14	26	CB-141414	
16x16x14	26	CB-161614	
18x18x12	24	CB-181812	
18x18x14	24	CB-181814	
18x18x16	24	CB-181816	
20x20x16	24	CB-202016	

END CAPS



End caps are 2" high, male end. Fabricated from galvanized steel meeting ASTM-A-653-96 standards in accordance with SMACNA gauge and construction standards.

Size	Gauge	Part #	QTY
5"	26	EC-C-05	
6"	26	EC-C-06	
7"	26	EC-C-07	
8"	26	EC-C-08	
9"	26	EC-C-09	
10"	26	EC-C-10	
12"	26	EC-C-12	
14"	26	EC-C-14	
16"	24	EC-D-16	
18"	24	EC-D-18	
20"	24	EC-D-20	
22"	24	EC-D-22	
24"	24	EC-D-24	
26"	24	EC-D-26	

DOVETAIL START COLLAR



Dovetail start collars are 5" high, crimped on one end. Fabricated from galvanized steel meeting ASTM-A-653-96 standards.

Size	Gauge	Part #	QTY
4"	26	SC-4	
5"	26	SC-5	
6"	26	SC-6	
7"	26	SC-7	
8"	26	SC-8	
9"	26	SC-9	
10"	26	SC-10	
12"	26	SC-12	
14"	26	SC-14	
16"	26	SC-16	
18"	26	SC-18	
20"	26	SC-20	
22"	26	SC-22	
24"	26	SC-24	
26"	26	SC-26	

AIR-TITE START COLLAR



Air-Tite start collars are 6" high with a 1.5" wide flange with adhesive gasket material, crimped on one end. Fabricated from galvanized steel meeting ASTM-A-653-96 standards with spot welded seams.

Size	Gauge	Part #	QTY
6"	26	ATSC-06	
7"	26	ATSC-07	
8"	26	ATSC-08	
9"	26	ATSC-09	
10"	26	ATSC-10	
12"	26	ATSC-12	
14"	26	ATSC-4	
16"	26	ATSC-16	
18"	26	ATSC-18	
20"	26	ATSC-20	

FLEX DUCT (25' LENGTH)



Foil-faced flexible duct manufactured by Atco Flex with a durable, scuff-resistant foil jacket, 1.5" thick blanket of fiberglass insulation, fiberglass threaded mesh, full internal poly liner which completely shields the air flow from fiberglass erosion and encapsulated, galvanized-coated, hard drawn spring wire.

R-value 6.0 UL-181 Class air duct, NFPA 90A and 90B

Size	Length	Part #	QTY
5"	25'	SAF25-05	
6"	25'	SAF25-06	
7"	25'	SAF25-07	
8"	25'	SAF25-08	
9"	25'	SAF25-09	
10"	25'	SAF25-10	
12"	25'	SAF25-12	
14"	25'	SAF25-14	
16"	25'	SAF25-16	
18"	25'	SAF25-18	
20"	25'	SAF25-20	

STOCK ACCESSORIES

PHOENIX



Screws	QTY
Drill Screw #10 x 1/2", 500pc	
Drill Screw #10 x 3/4", 500pc	

Duct Tapes	QTY
Polyken 339 Aluminum	
Tyco 555M Black Flex Fit	
Tyco 555M Silver Flex Fit	
Polyken 557 Metalized	
Polyken 557 Black	
Polyken 558CA	

Duct Sealants	QTY
DP1010 - 1 Gallon	
DP1010 - 10.67 Oz Tube	
DP1020 - 1 Gallon	
DP1020 - 10.67 Oz Tube	
Disposable Chip Brush	

Hanger Strap	QTY
26 Ga. - 1.5" x 80' roll	
26 Ga. - 1.5" x 80' roll with holes	
24 Ga. - 1.5" x 80' roll	

Fiberglass Duct Wrap	QTY
1" x 36" x 150' roll	
1" x 36" x 150' wrap (9" cuts)	
DP77 Spray Glue for Insulation	