





BUILDING BETTER.

STOCK ITEM CATALOG



SACRAMENTO FACILITY

1650 Parkway Boulevard, West Sacramento, CA 95691

CUSTOMER JOB INFORMATION SHEET

CUSTOMER INFORMATION

Customer Name

Address

City • State • Zip

Contact

Phone

JOB INFORMATION

Job Name

Address

City • State • Zip

Purchase Order #

Requested Delivery Date

Special Instructions

CATALOG INDEX

Item Description	Page #
Access Doors	18
Adjustable Elbows	5
Aluminum Flex	14
Bird Screen	17
Ceiling Boxes	11
Circle Liner	17
Damper Sleeves	8
Diffusers	18
Draw Bands	16
Drill Screws	15
Duct Mask	17
Duct Sealer	17
Duct Wrap	17
End Caps	11

Item Description	Page #
Flex Connector	17
Flex Duct	13
Hanger Strap	16
Hardware	15
KD Pipe	18
Reducers	9
Saddle Taps	10
Spiral Pipe	4
Start Collars	12
Stat Wire	16
T-Wyes	7
Tapes	17
Tie Wire	16

S-10 PIPE (10' LENGTHS)



8.5" wide strip, corrugated, crimped one end. S-10 (SMACNA) pipe is a lightweight yet very economical product used in most low pressure (2" static/water column) or less applications. Our SMACNA pipe (S10) is corrugated four times in between each spiral lockseam to increase the rigidity of the pipe. It is the lowest cost pipe we offer and it is very easy to handle and drill screws into. The consistent factory crimp eliminates the need for a coupling, reducing material & labor costs.

Size	Gauge	Part #	QTY
6"	28	S10-B-06	
7"	28	S10-B-07	
8"	28	S10-B-08	
9"	28	S10-B-09	
10"	28	S10-B-10	
12"	28	S10-B-12	
14"	28	S10-B-14	
16"	26	S10-C-16	
18"	26	S10-C-18	
20"	26	S10-C-20	
22"	26	S10-C-22	
24"	26	S10-C-24	
26"	24	S10-D-26	
28"	24	S10-D-28	

UMC PIPE (10' LENGTHS)



8.5" wide strip, smooth, crimped one end. 3" - 5" is a 5.394" wide strip. UMC pipe is gauged to meet Uniform Mechanical Code for up to +2" static/water column applications. UMC pipe also meets or exceeds SMACNA standards up to +10" static/water column and -2" static/water column applications. UMC pipe has a smooth finish and is factory crimped for faster installation.

Size	Gauge	Part #	QTY
3"	26	UMC-C-03	
4"	26	UMC-C-04	
5"	26	UMC-C-05	
6"	26	UMC-C-06	
7"	26	UMC-C-07	
8"	26	UMC-C-08	
9"	26	UMC-C-09	
10"	26	UMC-C-10	
12"	26	UMC-C-12	
14"	26	UMC-C-14	
16"	24	UMC-D-16	
18"	24	UMC-D-18	
20"	24	UMC-D-20	
22"	24	UMC-D-22	
24"	22	UMC-E-24	
26"	22	UMC-E-26	
28"	22	UMC-E-28	

90° - 4 GORE



90 Degree, 4 gore adjustable assembly from 3" to 20" diameters. 22" Diameter and above are 90 degree, 5 gore adjustable assembled. Crimped one end.

*Stainless Steel and Aluminum available upon request

Size	Gauge	Part #	QTY
3"	26	90-C-03	
4"	26	90-C-04	
5"	26	90-C-05	
6"	26	90-C-06	
7"	26	90-C-07	
8"	26	90-C-08	
9"	26	90-C-09	
10"	26	90-C-10	
12"	26	90-C-12	
14"	24	90-D-14	
16"	24	90-D-16	
18"	24	90-D-18	
20"	24	90-D-20	
22"	24	90-D-22	
24"	24	90-D-24	
26"	24	90-D-26	
28"	22	90-E-28	

45° - 2 GORE



45 Degree 2 gore adjustable assembly from 3" to 20" diameters., 22" Diameter and above are 45 degree, 3 gore adjustable assembled. Crimped one end.

*Stainless Steel and Aluminum available upon request

Size	Gauge	Part #	QTY
3"	26	45-C-03	
4"	26	45-C-04	
5"	26	45-C-05	
6"	26	45-C-06	
7"	26	45-C-07	
8"	26	45-C-08	
9"	26	45-C-09	
10"	26	45-C-10	
12"	26	45-C-12	
14"	24	45-D-14	
16"	24	45-D-16	
18"	24	45-D-18	
20"	24	45-D-20	
22"	24	45-D-22	
24"	24	45-D-24	
26"	24	45-D-26	
28"	22	45-E-28	

LONG RADIUS 90° - 5 GORE



90 Degree, 5 gore long radius adjustable assembly from 4" to 18" diameters. Crimped one end. 1.5 to 1 centerline radius.

*Stainless Steel and Aluminum available upon request

Size	Gauge	Part #	QTY
4"	26	90LR-C-04	
5"	26	90LR-C-05	
6"	26	90LR-C-06	
7"	26	90LR-C-07	
8"	26	90LR-C-08	
9"	26	90LR-C-09	
10"	26	90LR-C-10	
12"	26	90LR-C-12	
14"	24	90LR-D-14	
16"	24	90LR-D-16	
18"	24	90LR-D-18	
20"	24	90LR-D-20	

LONG RADIUS 45° - 3 GORE



45 Degree 3 gore long radius adjustable assembly from 3" to 20" diameters. Crimped one end. 1.5 to 1 centerline radius.

*Stainless Steel and Aluminum available upon request

Size	Gauge	Part #	QTY
4"	26	45LR-C-04	
5"	26	45LR-C-05	
6"	26	45LR-C-06	
7"	26	45LR-C-07	
8"	26	45LR-C-08	
9"	26	45LR-C-09	
10"	26	45LR-C-10	
12"	26	45LR-C-12	
14"	24	45LR-D-14	
16"	24	45LR-D-16	
18"	24	45LR-D-18	

STOCK T-WYES



All stock T-Wyes are spot welded with female/male/male ends. They are fabricated from galvanized steel meeting ASTM-A-653-96 standards.

Size	Gauge	Part #	QTY
8x6x6	26	Y-C-080606	
8x8x6	26	Y-C-080806	
8x8x8	26	Y-C-080808	
10x6x6	26	Y-C-100606	
10x8x6	26	Y-C-100806	
10x8x8	26	Y-C-100808	
10x10x6	26	Y-C-101006	
10x10x8	26	Y-C-101008	
10x10x10	26	Y-C-101010	
12x8x8	26	Y-C-120808	
12x10x6	26	Y-C-121006	
12x10x7	26	Y-C-121007	
12x10x8	26	Y-C-121008	
12x10x10	26	Y-C-121010	
12x12x10	26	Y-C-121210	
12x12x12	26	Y-C-121212	
14x10x10	26	Y-C-141010	
14x12x8	26	Y-C-141208	
14x12x10	26	Y-C-141210	
14x12x12	26	Y-C-141212	
14x14x6	26	Y-C-141406	

SACRAMENTO



Custom sizes and gauges available upon request.

Available with Jiffy dampers installed upon request.

Size	Gauge	Part #	QTY
14x14x8	26	Y-C-141408	
14x14x10	26	Y-C-141410	
14x14x12	26	Y-C-141412	
16x10x10	26	Y-C-161010	
16x12x10	26	Y-C-161210	
16x12x12	26	Y-C-161212	
16x14x8	26	Y-C-161408	
16x14x10	26	Y-C-161410	
16x14x12	26	Y-C-161412	
16x14x14	26	Y-C-161414	
16x16x10	26	Y-C-161610	
16x16x12	26	Y-C-161612	
18x14x12	26	Y-C-181412	
18x14x14	26	Y-C-181414	
18x16x10	26	Y-C-181610	
18x16x12	26	Y-C-181612	
18x16x14	26	Y-C-181614	
18x16x16	26	Y-C-181616	
18x18x10	26	Y-C-181810	
20x16x16	26	Y-C-201616	
20x18x16	26	Y-C-201816	

STOCK DAMPER SLEEVES

SACRAMENTO

SLEEVE - DAMPER



Sleeves are diameter plus 1" for overall length with 1.5" stand off, 3/8" aluminum rod with Rossi hardware. Sleeve is crimped on one end. All discs are 20 gauge to 14", 18 gauge 16" to 20". All sleeves fabricated from galvanized steel meeting ASTM-A-653-96 standards.

Duro-Dyne hardware upon request.

Size	Gauge	Part #	QTY
6"	24	DS1.5-062	
7"	24	DS1.5-072	
8"	24	DS1.5-082	
9"	24	DS1.5-092	
10"	24	DS1.5-102	
12"	24	DS1.5-C-122	
14"	24	DS1.5-D-142	
16"	24	DS1.5-D-162	
18"	24	DS1.5-D-182	
20"	24	DS1.5-D-202	

SLEEVE - JIFFY DAMPER



Sleeves are diameter plus 2" for overall length. We use Duro-Dyne RS256 Jiffy hardware. All sleeves fabricated from galvanized steel meeting ASTM-A-653-96 standards.

Size	Gauge	Part #	QTY
4"	26	DS-04	
5"	26	DS-05	
6"	26	DS-06	
7"	26	DS-07	
8"	26	DS-08	
9"	26	DS-09	
10"	26	DS-10	
12"	26	DS-12	
14"	24	DS-14	
16"	24	DS-16	
18"	24	DS-18	
20"	24	DS-20	

3-PIECE REDUCERS




Stock 3-piece reducers have a 6" taper and 3" long collars on both ends. All 3-piece reducers are fabricated from galvanized steel meeting ASTM-A-653-96 standards in accordance with SMACNA gauge and construction standards.

Size	Gauge	Part #	QTY
6x4	26	R06-C-0604	
6x5	26	R06-C-0605	
8x6	26	R06-C-0806	
8x7	26	R06-C-0807	
9x8	26	R06-C-0908	
10x6	26	R06-C-1006	
10x7	26	R06-C-1007	
10x8	26	R06-C-1008	
10x9	26	R06-C-1009	
12x8	26	R06-C-1208	
12x10	26	R06-C-1210	
14x8	26	R06-C-1408	
14x10	26	R06-C-1410	
14x12	26	R06-C-1412	

Size	Gauge	Part #	QTY
16x10	24	R06-D-1610	
16x12	24	R06-D-1612	
16x14	24	R06-D-1614	
18x14	24	R06-D-1814	
18x16	24	R06-D-1816	
20x16	24	R06-D-2016	
20x18	24	R06-D-2018	
22x20	24	R06-D-2220	
24x22	24	R06-D-2422	
26x24	24	R06-D-2624	

SADDLE TAP ON ROUND




Saddle taps on round have a 45 degree branch and are fabricated from galvanized steel meeting ASTM-A-653-96 standards in accordance with SMACNA gauge and construction standards.

*Jiffy dampers installed upon request

Size	Gauge	Part #	QTY
6 on 10	26	STCR45-C-0610	
8 on 10	26	STCR45-C-0810	
8 on 12	26	STCR45-C-0812	
8 on 14	26	STCR45-C-0814	
10 on 12	26	STCR45-C-1012	
10 on 14	26	STCR45-C-1014	
10 on 16	26	STCR45-C-1016	
12 on 14	26	STCR45-C-1214	
12 on 16	26	STCR45-C-1216	
14 on 18	26	STCR45-C-1418	

SADDLE TAP ON FLAT



Saddle taps on flat have a 45 degree branch and are fabricated from galvanized steel meeting ASTM-A-653-96 standards in accordance with SMACNA gauge and construction standards.

*Jiffy dampers installed upon request

Size	Gauge	Part #	QTY
6"	26	STCF45-C-06	
8"	26	STCF45-C-08	
10"	26	STCF45-C-10	
12"	26	STCF45-C-12	
14"	26	STCF45-C-14	

STOCK CEILING BOXES & END CAPS

SACRAMENTO

CEILING BOXES



Ceiling boxes have a 4" high can plus a 3" high collar and a plaster ground. Fabricated from galvanized steel meeting ASTM-A-653-96 standards in accordance with SMACNA gauge and construction standards.

Size	Gauge	Part #	QTY
6x6x5	26	CB-060605	
6x6x6	26	CB-060606	
8x8x6	26	CB-080806	
8x8x7	26	CB-080807	
8x8x8	26	CB-080808	
10x10x6	26	CB-101006	
10x10x8	26	CB-101008	
10x10x10	26	CB-101010	
12x12x6	26	CB-121206	
12x12x8	26	CB-121208	
12x12x10	26	CB-121210	
12x12x12	26	CB-121212	
14x14x10	26	CB-141410	
14x14x12	26	CB-141412	
14x14x14	26	CB-141414	
16x16x12	26	CB-161612	
16x16x14	26	CB-161614	
18x18x12	24	CB-181812	
18x18x14	24	CB-181814	

END CAPS



End caps are 2" high, male end. Fabricated from galvanized steel meeting ASTM-A-653-96 standards in accordance with SMACNA gauge and construction standards.

Size	Gauge	Part #	QTY
5"	26	EC-C-05	
6"	26	EC-C-06	
7"	26	EC-C-07	
8"	26	EC-C-08	
9"	26	EC-C-09	
10"	26	EC-C-10	
12"	26	EC-C-12	
14"	26	EC-C-14	
16"	24	EC-D-16	
18"	24	EC-D-18	
20"	24	EC-D-20	
22"	24	EC-D-22	
24"	24	EC-D-24	
26"	24	EC-D-26	

STOCK START COLLARS

SACRAMENTO

DOVETAIL START COLLAR



Dovetail start collars are 5" high, crimped on one end. Fabricated from galvanized steel meeting ASTM-A-653-96 standards.

Size	Gauge	Part #	QTY
4"	26	SC-4	
5"	26	SC-5	
6"	26	SC-6	
7"	26	SC-7	
8"	26	SC-8	
9"	26	SC-9	
10"	26	SC-10	
12"	26	SC-12	
14"	26	SC-14	
16"	26	SC-16	
18"	26	SC-18	
20"	26	SC-20	
22"	26	SC-22	
24"	26	SC-24	
26"	26	SC-26	


AIR-TITE START COLLAR



Air-Tite start collars are 6" high with a 1.5" wide flange with adhesive gasket material, crimped on one end. Fabricated from galvanized steel meeting ASTM-A-653-96 standards with spot welded seams.

Size	Gauge	Part #	QTY
4"	26	ATSC-04	
5"	26	ATSC-05	
6"	26	ATSC-06	
7"	26	ATSC-07	
8"	26	ATSC-08	
9"	26	ATSC-09	
10"	26	ATSC-10	
12"	26	ATSC-12	
14"	26	ATSC-4	
16"	26	ATSC-16	
18"	26	ATSC-18	
20"	26	ATSC-20	

6' LENGTH WITH COLLARS



Foil-faced flexible duct manufactured by Atco Flex with a durable, scuff-resistant foil jacket, 1.5" thick blanket of fiberglass insulation, fiberglass threaded mesh, full internal poly liner which completely shields the air flow from fiberglass erosion and encapsulated, galvanized-coated, hard drawn spring wire.

R-value 6.0 UL-181 Class air duct, NFPA 90A and 90B.
R-value 8.0 on request.

Size	Length	Part #	QTY
5"	6'	SAF6-05	
6"	6'	SAF6-06	
7"	6'	SAF6-07	
8"	6'	SAF6-08	
9"	6'	SAF6-09	
10"	6'	SAF6-10	
12"	6'	SAF6-12	
14"	6'	SAF6-14	
16"	6'	SAF6-16	
18"	6'	SAF6-18	
20"	6'	SAF6-20	

25' LENGTH



Foil-faced flexible duct manufactured by Atco Flex with a durable, scuff-resistant foil jacket, 1.5" thick blanket of fiberglass insulation, fiberglass threaded mesh, full internal poly liner which completely shields the air flow from fiberglass erosion and encapsulated, galvanized-coated, hard drawn spring wire.

R-value 6.0 UL-181 Class air duct, NFPA 90A and 90B.
R-value 8.0 on request.

Size	Length	Part #	QTY
4"	25'	SAF25-04	
5"	25'	SAF25-05	
6"	25'	SAF25-06	
7"	25'	SAF25-07	
8"	25'	SAF25-08	
9"	25'	SAF25-09	
10"	25'	SAF25-10	
12"	25'	SAF25-12	
14"	25'	SAF25-14	
16"	25'	SAF25-16	
18"	25'	SAF25-18	
20"	25'	SAF25-20	
22"	25'	SAF25-22	

INSULATED ALUMINUM FLEX



Aluminum flex has a durable scuff-resistant silver foil jacket with a 1.5" thick blanket of fiberglass insulation. Joints are 6' long with collars on both ends.

R-value 6.0 UL-181 Class air duct, NFPA 90A and 90B

Size	Length	Part #	QTY
5"	6'	OFD3-05	
6"	6'	OFD3-06	
7"	6'	OFD3-07	
8"	6'	OFD3-08	
9"	6'	OFD3-09	
10"	6'	OFD3-10	
12"	6'	OFD3-12	
14"	6'	OFD3-14	
16"	6'	OFD3-16	
18"	6'	OFD3-18	
20"	6'	OFD3-20	

BARE ALUMINUM FLEX



Bare aluminum flex with no insulation. 3" - 4" diameters are 10' long with raw ends. 5" - 14" diameters are 6' long with collars on both ends.

Size	Length	Part #	QTY
3"	10'	OFD110R-03	
4"	10'	OFD110R-04	
5"	6'	OFD1-05	
6"	6'	OFD1-06	
7"	6'	OFD1-07	
8"	6'	OFD1-08	
9"	6'	OFD1-09	
10"	6'	OFD1-10	
12"	6'	OFD1-12	
14"	6'	OFD1-14	
16"	6'	OFD1-16	
18"	6'	OFD1-18	
20"	6'	OFD1-20	

Screws	POINT	PCS	QTY
#8 x 1/2"	Drill	500	
#8 x 1/2"	Taper	1000	
#8 x 3/4"	Drill	500	
#8 x 3/4"	Taper	1000	
#8 x 1"	Taper	1000	
#8 x 1-1/2"	Taper	500	
#8 x 2"	Taper	500	
#10 x 1/2"	Drill	500	
#10 x 3/4"	Drill	500	
#10 x 3/4"	Drill	1000	
#10 x 3/4"	Drill	5000	
#10 x 1"	Drill	500	
#10 x 1"	Drill	1000	

Washers	Part #	QTY
3/8"	E-147-38	
1/2"	E-147-12	

Bolts	Part #	QTY
3/8" x 1"	E-142-381	
3/8" x 1-1/2"	E-142-3812	
1/2" x 1-1/2"	E-142-12112	
1/2" x 2"	E-142-122	

Nuts	Part #	QTY
3/8"	E-145-38	
1/2"	E-145-12	

Ventifabrics Hardware	QTY
Ventilock O.E.B. #607	
Ventilock O.E.B. #641	
Ventilock Dial #638	

Sammy Hardware	Part #	QTY
Sammy 3/8" 25pk	SAMMY-3/8"	

STOCK HANGER STRAP & WIRE

SACRAMENTO

Hanger Strap	QTY
26 Ga. - 1.5" x 80' roll	
26 Ga. - 1.5" x 80' roll with holes	
24 Ga. - 1.5" x 80' roll	

Hanger Strap 1" 10pc Bundle	Part #	QTY
24 GA	HS-24	
22 GA	HS-22	
20 GA	HS-20	
18 GA	HS-18	
16 GA	HS-16	

Hanger Strap 1.5" 10pc Bundle	Part #	QTY
24 GA	HS1.5-24	
22 GA	HS1.5-22	
20 GA	HS1.5-20	
18 GA	HS1.5-18	
16 GA	HS1.5-16	

Draw Bands	Part #	QTY
36"	DB36	
48"	DB48	
Stainless	SSDB	

Tie Wire	Part #	QTY
18 GA roll	TIEWIRE	
16 GA roll	TW	

Hanger Wire	Part #	QTY
12'x100pc 12 GA	HW10	

Stat Wire 18 GA	ROLL	Part #	QTY
18-2	500'	SW-182	
18-3	500'	SW-183	
18-4	250'	SW-184	
18-5	250'	SW-185	
18-6	250'	SW-186	
18-7	250'	SW-187	
18-8	250'	SW-188	

Tapes	QTY
FSK Tape 338	
Ideal 3" Foil Tape	
Polyken 339 Aluminum	
Tyco 555M Black Flex Fit	
Tyco 555M Silver Flex Fit	
Polyken 557 Metalized	
Polyken 557 Black	
Polyken 558CA	
Flagging Tape 150' Roll	
Hardcast Red AFG-1402	

Duct Sealants	QTY
DP1010 - 1 Gallon	
DP1010 - 10.67 Oz Tube	
DP1020 - 1 Gallon	
DP1020 - 10.67 Oz Tube	
VG181 - 1 Gallon	
VG181 - 10.67 Oz Tube	
Disposable Chip Brush	

Flex Connector	Part #	QTY
3" x 3" x 3"	MBX4	
4" x 4" x 4"	MBX444	

Circle Liner 1" x 6' Length	Part #	QTY
8" OD - 6" ID	CCL1-0806	
9" OD - 7" ID	CCL1-0907	
10" OD - 8" ID	CCL1-1008	
12" OD - 10" ID	CCL1-1210	
14" OD - 12" ID	CCL1-1412	
16" OD - 14" ID	CCL1-1614	
18" OD - 16" ID	CCL1-1816	
20" OD - 18" ID	CCL1-2018	
22" OD - 20" ID	CCL1-2220	

Fiberglass Duct Wrap	QTY
1" x 150' roll	
1" x 150' wrap (9" cuts)	
1-1/2" x 150' roll	
2" x 150' roll	
3" x 150' roll	
DP77 Spray Glue for Insulation	

Bird Screen 48" x 100' Rolls	QTY
1/4" Wire Mesh 23 GA	
1/2" Wire Mesh 19 GA	
1" Wire Mesh 14 GA	

Duct Mask	Part #	QTY
24"	24MASK	
36"	36MASK	
48"	48MASK	

KD Pipe 24 GA - 3' Length	Part #	QTY
26"	BL-D-26	
24"	BL-D-24	
22"	BL-D-22	
20"	BL-D-20	
18"	BL-D-18	

Curved Blade Diffusers 24" x 24"	Part #	QTY
6"	CBS-06	
8"	CBS-08	
10"	CBS-10	
12"	CBS-12	
14"	CBS-14	

KD Pipe 26 GA - 5' Length	Part #	QTY
5"	BL5-C-05	
6"	BL5-C-06	
7"	BL5-C-07	
8"	BL5-C-08	
9"	BL5-C-09	
10"	BL5-C-10	
12"	BL5-C-12	
14"	BL5-D-14	

Return Air Diffusers 24" x 24"	Part #	QTY
6"	RA-06	
10"	RA-10	
12"	RA-12	
14"	RA-14	

Insulated Access Door Round Duct	Part #	QTY
4"x8" for 5" - 6"	RAD-48-6	
4"x8" for 7" - 8"	RAD-48-9	
4"x8" for 10" - 11"	RAD-48-11	
4"x8" for 12" - 14"	RAD-48-14	
8"x12" for 11"	RAD-812-11	
8"x12" for 14"	RAD-812-14	
8"x12" for 16"	RAD-812-16	
8"x12" for 18"	RAD-812-18	

Hinged Access Door	Part #	QTY
6"	PAC-6	
8"	PAC-8	
10"	PAC-10	
12"	PAC-12	
14"	PAC-14	
16"	PAC-16	
18"	PAC-18	

Insulated Access Door Rectangular Duct	Part #	QTY
10" x 6"	DMA-1006	
12" x 8"	DMA-1208	
18" x 14"	DMA-1814	